EPOXY-GRIP SPRAY COATING

Black Anti-Slip Coating

Form: Aerosol Liquid

Color: Black

Odor: Characteristic

pH: N/A

Solubility (in water): Insoluble
(in mineral spirits): Soluble

Viscosity (CPS at 70°F): >40

Flash Point (ASTM D-7821): -2°F (conc.)

Specific Gravity: N/D

Density: N/D

Storage Stability (at 70°F): 1 year

Ingredients	C.A.S. #
Acetone	67-64-1
Xylene	1330-20-7
Methyl Iso-Butyl Ketone	108-10-1
Ethyl Benzene	100-41-4
Mineral Spirits	64742-47-8

Great for use on...

- **Steps**
- **Ramps**
- **Showers**
- **Loading Docks**
- **Ladders**
- **Running Boards**
- **Boats**
- **Decks**

Coverage: Approximately 12-16 sq. ft.

Grit Size: 90 Micron

PREPARATION: Surface must be clean and dry before painting. For best results, use when can is between 70° and 90°F. (21° and 32°C). Previously painted surfaces should be cleaned with a mild detergent, rinsed thoroughly and dried. Before initial application, a light etch or sanding is recommended. Test a small area for compatibility and adhesion. The coating is self priming on most surfaces.

APPLICATION: Shake can at least one minute before and occasionally during use. Spray surface with steady, even strokes at a distance of 8 to 10 inches (20 to 25 cm). Several light coats give a better finish than one heavy coat. If clogging develops, turn spray button ¼ turn or remove and clean button slot. Do not stick objects into can opening. After painting, turn can upside down and spray for 2 seconds to clean spray button. Discard empty can in trash pick up. Don not incinerate or compact.

DRYTIME: Dries to the touch in approximately 30 minutes. Be sure the first coat is dry before applying a second coat. The rate of cure will vary with the film thickness, temperature and humidity. Allow 24 hours before opening to heavy foot traffic. Recoat in 3 to 6 months or as wear indicates.

HMIS				NFPA
	Severe	4	Extreme	
Health 1	Serious	3	High	Health 1
Flammability 4	Moderate	2	Moderate	Flammability 4
Reactivity 3	Slight	1	Slight	Reactivity 3
Personal Protection X	Minimal	0	Insignificant	Special Precautions ..... None

Share Corporation • P.O. Box 245013 • Milwaukee, WI 53224 • 800-776-7192