INHIBITED WATER METER CLEANER

Inhibited Acid Cleaner

Form: Liquid Color: Green

Odor: Sharp Acid

pH: <1.00

Solubility (in water): Soluble **(in mineral spirits):** Insoluble

Viscosity (CPS at 70° F): >40

Flash Point (ASTM D-7821): N/A

Specific Gravity: 1.10 ± 0.05 lbs/gal

Density: $9.18 \pm 0.05 \text{ g/cm}^3$

Storage Stability (at 70°F): 1 year

<u>Ingredients</u>	C.A.S. #
Hydrochloric Acid	7647-01-0
Water	7732-18-5
Poly (oxyethylene) nonylphenol	9016-45-9
Ethoxylated Amine Resin	61791-17-1
Acid Green DyeNo C.A	S. Number

Other Uses...

- Coil Delimer
- Pool Conditioner
- Tile and Grout Cleaner
- Ammonia Neutralizer
- Dairy Tank Cleaner
- Kennel Cleaner

DIRECTIONS: To clean and descale water meters and metal parts, submerge parts in undiluted INHIBITED CHEMICAL WATER METER CLEANER and soak until all deposits are dissolved. Rinse thoroughly with clean water. For light deposits, dilute INHIBITED CHEMICAL WATER METER CLEANER with 3 to 5 parts water. To descale boilers, cooling towers, condensers, heat exchangers, and other water handling systems, dilute INHIBITED CHEMICAL WATER METER CLEANER with 8 to 10 parts water. Allow solution to soak or circulate in system for 4 to 8 hours, until scale is removed. Flush system thoroughly with clean water. Rinse empty container before disposal.

HMIS				NFPA
	Severe	4	Extreme	
Health2	Serious	3	High	Health 2
Flammability0	Moderate	2	Moderate	Flammability0
Reactivity1	Slight	1	Slight	Reactivity1
Personal ProtectionX	Minimal	0	Insignificant	Special PrecautionsNone