







PO BOX 245013 MILWAUKEE, WI 53224 800.776.7192 www.sharecorp.com



**DYNASTY X-FLUSH** is non-toxic, non-pathogenic, safe, effective in sewage systems and it contains no acids or caustic materials and will not harm plumbing fixtures

## DISPOSAL:

Offer empty container for recycling. If recycling is not available, discard container in trash.

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

## NFPA® Ratings

Health: 0: Flammability: 0: Reactivity: 0

**DYNASTY X-FLUSH** is safe for use in X-ray, CAT scan and MRI (Magnetic Resonance Imaging) drain systems.

**DYNASTY X-FLUSH** will digest fats, animal, vegetable and mineral oils, greases, cellulose, starches, proteins and carbohydrates into carbon dioxide and water.

## **DIRECTIONS:**

For X-Ray drains and sinks: Add an initial treatment of 1 gallon of DYNASTY X-FLUSH, then 30 ounces per day for 6 weeks. After 6 weeks, DYNASTY X-FLUSH addition may be reduced to 20 ounces per day. Addition of DYNASTY X-FLUSH should be at the end of the day or during periods of lowest flow through drains.

DYNASTY X-FLUSH may be used through the "Bio-Drain Station" which dispenses product at a rate of 5 ounces per minute. Use the chart below as a guide for using DYNASTY X-FLUSH through the "Bio-Drain Station".

Pipe Size	Dosage	Bio-Drain Statio Run Time
	5 ounces / day	1 minute / day
4 inches	10 ounces / day	2 minutes / day
6 inches	15 ounces / day	3 minutes / day
8 inches	20 ounces / day	4 minutes / day

## INGREDIENTS/CAS #:

Water (7732-18-5); Polysorbate 20 (9005-64-5); Tetrasodium EDTA (64-02-8); Bacterial Mixture (Not Available); Styrene Acrylates Copolymer (9010-92-8).



0532.012022