



PELLET DEICER

FAST ACTING ICE MELT PELLETS FOR USE ON ALL TRAFFIC AREAS



WARNING: Harmful if swallowed. Causes skin irritation. Causes eye irritation.

PREVENTION: Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wear eye protection, face protection, protective gloves.

IF SWALLOWED: Call a doctor, a POISON CENTER if you feel unwell. Rinse mouth.

IF ON SKIN: Wash with plenty of water.

If skin irritation occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice or attention.

In case of fire: Adapt extinguishing media to the environment.

DISPOSAL: Offer empty container for recycling. If recycling is not available, discard container in trash.

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

NFPA® RATINGS:

Health: 1; Flammability: 0; Reactivity: 0

INGREDIENTS/CAS #:

Calcium Chloride (10043-52-4); Water (7732-18-5); Potassium Chloride (7447-40-7); Sodium Chloride (7647-14-5).

PELLET DEICER quickly melts ice and packed snow from sidewalks, driveways, steps, porches, parking lots, loading docks, ramps, drain pipes and eaves.

PELLET DEICER is much more effective than ordinary salt or sand - it melts ice even at -50° F, and won't harm skin, clothing or lawns when used as directed.

DIRECTIONS: Sprinkle **PELLET DEICER** evenly over ice or packed snow, allow it to act for several minutes, then remove melted slush. **PELLET DEICER** is not corrosive and is safe to use on concrete, brick, cement, flagstone and asphalt. However, spalling or flaking of these surfaces may occur due to natural deterioration from freeze/thaw cycles. While such instances are rare, they involve factors over which the manufacturer has no control, and the use of **PELLET DEICER** must be at the user's risk.

NOTE: **PELLET DEICER** should not be used on concrete less than one year old and should not be used on concrete with exposed aggregate, precast steps.



Please Recycle.

0600.100121

Net Contents: 50 ■ 80 ■ 100 ■ Pounds