

# **DIESEL FUEL PERFORMANCE CONDITIONER**

- Boosts Cetane Levels up to 3 to 5 Points.
- · Lowers pour point by 15 to 25 degrees F.
- Can Prevent Fuel Gelling and Icing down to -40 F.
- . Cleans up Injectors and Prevents Deposits.
- Increases Lubricity in Low Sulfur Fuels.
- Protects, Adds Lubricity to Injectors and Fuel Pumps. Can Aid in the Prevention of Sludge Build Up.
- Improves Fuel Economy, Boosts MPG.
- Moisture Dispersant Controls Water and Corrosion.
- Improves Cold Starts.
- Reduces Soot and Black Smoke.
- Stabilizes Diesel for Storage.

### WARNING

Flammable liquid and vapour. Harmful if swallowed, in contact with skin or if inhaled. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. May cause cancer.

## **KEEP OUT OF REACH OF CHILDREN**

**Net Contents: One Quart** 







#### WARNING:

Flammable liquid and vapour, Harmful if swallowed, in contact with skin or if inhaled. Causes skin irritation. Causes serious eve irritation. May cause respiratory irritation. May cause drowsiness or dizziness. May cause cancer.

#### PREVENTION:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat. hot surfaces, sparks, open flames and other ignition sources. No smoking, Keep container tightly closed, Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/ lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/ mist/vapours/spray, Wash thoroughly after handling, Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

IF SWALLOWED: Immediately call a poison center or doctor. IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse. If exposed or concerned: Get medical advice/attention. Call a poison center or doctor if you feel unwell.

In case of fire: Use media other than water to extinguish.

PRO DIESEL is a multi-functional diesel fuel supplement that can improve performance in all diesel engines, in over-the-road rigs, delivery trucks. construction equipment, farm equipment, autos, pick-up trucks and stationary diesel engines that power pumps and generators.

From the first time you add PRO DIESEL, your diesel engines will achieve optimum performance, improved starting and a marked increase in power. PRO DIESEL increases cetane, lowers pour point, prevents gelling down to -40 F., improves fuel stability, adds lubricity, detergency and water control. With continued use, PRO DIESEL protects and cleans vital engine components, while maintaining fuel economy and reducing emissions. It's the most complete additive package you can use.

#### DIRECTIONS:

BULK STORAGE TANK: Normal Operation, Add 1 Gallon of PRO DIESEL to 2,000 gallons of Diesel Fuel.

Cold Weather Operation, Add 1 gallon of PRO DIESEL to 1,000 gallons of Diesel Fuel, Add directly to Storage Tank,

VEHICLE OR MACHINE FUEL TANK: Normal Operation, Add 1 Quart of PRO DIESEL to 250 to 450 gallons of Diesel Fuel.

Cold Weather Operation, Add 1 Quart of PRO DIESEL to 150 to 250 gallons of Diesel Fuel. Add directly to Fuel Tank.

Use in ULSD Blends up to B20.

#### **NFPA® RATINGS**

Health: 3: Flammability: 2: Reactivity: 0

#### INGREDIENTS/CAS #:

Solvent naphtha, petroleum, light arom, (64742-95-6); 2-Ethylhexyl nitrate (27247-96-7); Solvent naphtha, petroleum, heavy arom, (64742-94-5); 1.2.4-Trimethylbenzene (95-63-6); 2-Butoxyethanol (111-76-2).

For industrial and commercial use only.

For additional information, see Safety Data Sheet,

Store in a well-ventilated place. Keep container tightly closed. Keep cool, Store locked up.

Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

WARNING: This product can expose you to naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

0658.031020

Share Corp. • P.O. Box 245013 • Milwaukee, WI 53224 • (800) 776-7192 • www.sharecorp.com