

NON-ACID
SHARE LIME AND
SCALE REMOVER



Causes serious eye irritation. Suspected of causing cancer.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: □1 □ 5 □ 20 □ 35 □ 55 Gallon(s)



PO BOX 245013 MILWAUKEE, WI 53224 800.776.7192 www.sharecorp.com



WARNING:

Causes serious eye irritation. Suspected of causing cancer.

PREVENTION:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash thoroughly after handling. Wear eye protection, protective clothing, protective gloves.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention.

Store locked up.

Dispose of contents/container to comply with local/regional/national/international regulations.

MARNING:

This product can expose you to Ethylene Oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

NON-ACID LIME AND SCALE REMOVER represents a new concept in formulated chemical cleaners. An inhibited blend of powerful cleaning agents is transformed into an effective but easy to handle cleaner.

NON-ACID LIME AND SCALE REMOVER may be used for dissolving scale, mineral, or lime deposits that form on metal, machinery or parts- also for cleaning radiators and cooling systems. Simply apply NON-ACID LIME AND SCALE REMOVER, allow to remain for a short period, and rinse with water. For more stubborn cases completely immerse part in NON-ACID LIME AND SCALE REMOVER and allow to soak overnight. Prolonged contact will not harm metal surface. For aluminum - Apply with mop, brush or sponge. Rinse thoroughly within 3 minutes after application. Test a small area before using on anodized aluminum.

NON-ACID LIME AND SCALE REMOVER is excellent for descaling condensers, heat exchangers, and water meters. It may also be used to clean and remove scale from an entire cooling tower system.

NFPA* RATINGS

Health: 1; Flammability: 0; Reactivity: 0

INGREDIENTS/CAS #:

Water (7732-18-5); Pentasodium Triphosphate (7758-29-4); Tetrasodium EDTA (64-02-8); Sodium Laureth Sulfate (9004-82-4); Sodium Glycolate (2836-32-0); Sodium Hydroxide (1310-73-2).



ase Recycle

1401.102721