

# HEAVY DUTY INDUSTRIAL CLEANER

# Extratoam

MULTI-PURPOSE ALKALINE CLEANER CONCENTRATE
BIODEGRADABLE • WATER SOLUBLE • NON-FLAMMABLE

## DANGER

May be corrosive to metals. Causes skin irritation

Causes serious eye damage. Suspected of causing cancer.

May cause damage to organs through prolonged or repeated exposure.

# **KEEP OUT OF REACH OF CHILDREN**

NET CONTENTS: 0 1 0 5 0 20 0 35 0 55 Gallon(s)





PO BOX 245013 MILWAUKEE, WI 53224 800.776.7192 www.sharecorp.com



### DANGER:

May be corrosive to metals. Causes skin irritation.
Causes serious eye damage. Suspected of causing cancer
May cause damage to organs through prolonged or
repeated exposure.

### PREVENTION:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep only in original container. Do not breathe mist, spray. Wash thoroughly after handling. Wear eyelprotection, protective clothing, protective gloves. Take off contaminated clothing and wash before reuse.

IF ON SKIN: Wash with plenty of water.

If skin irritation occurs: Get medical advice/attention.
If exposed or concerned: Get medical advice/attention.
IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor, a POISON CENTER. Get

medical advice/attention if you feel unwell.

Absorb spillage to prevent material damage.

Store locked up. Store in corrosive resistant container with a resistant inner liner.

Dispose of contents/container to comply with local/regional/national/international regulations.

HDIC EXTRA FOAM is a versatile cleaner designed to remove wax, soil, grease, and grime from any water washable surface. Specially incorporated foaming agents generate an explosive foaming action for applications using foam generators, or where more sudsing action is desired. This highly concentrated formula allows the user to accomplish a multitude of cleaning chores with a single product!

### DIRECTIONS:

Dilute **HDIC EXTRA FOAM** with clean, hot water to a strength appropriate for the job. Recommended dilutions range from 1:20 for cleaning floors, walls, files, and decorative surfaces to 1:8 for cleaning greasy fans, swimming pools, and white walls. Spray mop, or sponge solution on to surface to be cleaned, and allow several minutes to penetrate deposits. Rinse surface thoroughly with water. Thick deposits may require gentle scrubbing or a stronger solution.

### NFPA® RATINGS

Health: 2: Flammability: 1: Reactivity: 0

### INGREDIENTS/CAS #:

Water (7732-18-5); 2-butoxyethanol (111-76-2); Sodium Tripolyphosphate (7758-29-4); Potassium Hydroxide (1310-58-3); Sodium Metasilicate (6834-92-0); Cocoamide (8051-30-7): Diethanolamine (111-42-2).

### **WARNING:**

This product can expose you to ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

For industrial and commercial use only.

For additional information, see Safety Data Sheet.



1413.060115