

# HI TEMP RED GREASE AEROSOL

MULTI-SERVICE NON-MELT LUBRICANT

PREVENTS RUST
PENETRATES AS !T LUBRICATES
CONTAINS NO FLUORINATED SOLVENTS

# DANGER:

Extremely flammable aerosol. Contains gas under pressure: May explode if heated.

**KEEP OUT OF REACH OF CHILDREN** 

Net Weight: 15 ounces (425 g)

HI TEMP RED GREASE AEROSOL is a USDA authorized multipurpose lubricant that changes from a penetrating fluid to a strong, long-lasting grease in one to two minutes. The slower cure time allows the lubricant to penetrate into hard-to-reach areas. The cured grease withstands temperatures up to 500°F, high pressure, acids, and moisture. Excellent for use on chains, cables, winches, conveyors, gears, bushings, pins, rollers, tools, hinges and much more.









# **DANGER:**

Extremely flammable aerosol contains gas under pressure: May explode if heated. Causes skin and eye irritation. Supported of causing cancer. May cause drowliness and dizziness. May be fatal if swallowed and entersairman

## PREVENTION:

Keep away from heat, sparks, open filmles, and hot surfaces.

No smoking. Do not spray on an overlyflame or other ignition soutce. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight Do not expose to temperatures exceeding 50°C/12°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves. Avoid breathing funds, vapors, and spray.

# RESPONSE

induce vomiting.

**If on skin:** Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash

If in eyes: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

If swallowed: Immediately call a poison center or doctor. Do NOT

**If inhaled:** Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical advice or attention. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations.

### **INGREDIENTS/CAS#:**

Heptane (142-82-5); Heavy Naphthenic Petroleum Distillate (64742-52-5); Propane/n-Butane (68476-86-8); Tetrachloroethylene (127-18-4); Organophilic Clay (N/A).

# NFPA® RATINGS:

Health: 2; Flammability: 3; Reactivity: 0

### **DIRECTIONS:**

Shake Well Before Using. Remove cap and hold can approximately 6 to 8 inches from surface to be sprayed. Apply a light coat by spraying in quick, short bursts. Work part to distribute **HI TEMP RED GREASE AEROSOL** evenly over the entire surface. For hard-to-reach areas, insert the red extender tube into the tip. Spray as necessary to insure complete coverage. Temperatures over 375°F may require periodic reapplication.

**WARNING:** This product contains a chemical(s) known to the State of California to cause cancer.

old by: 8011.021815

Share Corp. • P.O. Box 245013 • Milwaukee, WI 53224 • (800) 776-7192 • www.sharecorp.com