

OPEN GEAR LUBE AEROSOL

High Adhesion Lubricant

Form: Asphalt like

Color: Black

Odor: Petroleum Solvent

pH: N/A

Solubility (in water): Insoluble
(in mineral spirits): Soluble

VOC Content (% by weight): 43.5%

Flash Point (ASTM D-7821): 122°F

Specific Gravity: 0.82 g/cm³

Density: 6.84 lbs/gal

Storage Stability (at 70°F): 1 year

Ingredients

C.A.S. #

Petroleum Resins	64742-16-1
Heptane	142-82-5
Hydrotreated Petroleum Oils	64742-57-0
Propane/n-butane	68476-86-8

Great for...

- **Foundries**
- **Automobile applications**
- **Agricultural applications**
- **Heavy construction applications**
- **Industrial applications**
- **HVAC applications**
- **Metal manufacturers**

Provides protection for...

- | | |
|------------------|-------------------------|
| • Gears | • Scrapers |
| • Winches | • Motors |
| • Cranes | • Press fittings |
| • Pumps | • Compressors |
| • Plows | • Chains |
| • Dozers | • Cables |
| • Loaders | • Wire ropes |
| • Graders | • Sprockets |

DIRECTIONS: Shake Well Before Using. Remove cap and hold can approximately 6 to 8 inches from surface to be sprayed. Apply a continuous film of lubricant, turn on machinery, and allow the lubricant to spread over all working surfaces. Apply a second, thinner coat to insure adequate protection. Reapply as needed. After spraying, turn can upside down and spray for a few seconds until the nozzle is clear.

Note: Temperature Range is +20° to +175°F.

HMIS				NFPA	
		Severe	4	Extreme	
Health	1	Serious	3	High	Health..... 1
Flammability.....	3	Moderate	2	Moderate	Flammability..... 3
Reactivity.....	1	Slight	1	Slight	Reactivity..... 1
Personal Protection	B	Minimal	0	Insignificant	Special Precautions.....None