



four way ACTION NC

NON-CHLORINATED PENETRANT & RUST PREVENTATIVE

- Quickly Penetrates Rust
- Creates Moisture Barrier
- Lubricates and Prevents Corrosion
 - Non-Flammable
- Non-Conductive, High Dielectric Strength: 39,000V

DANGER

Contains gas under pressure; may explode if heated.

KEEP OUT OF REACH OF CHILDREN

See side panel for additional precautions.

Net Wt. 17 oz. (482 g)



DANGER:

Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Suspected of damaging fertility or the unborn child.

PREVENTION:

Keep away from heat, sparks, open flames, hot surfaces.
- No smoking. Pressurized container: Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all precautions have been read and understood. Wear protective gloves, clothing and eye protection. If exposed or concerned: Get medical attention.

RESPONSE:

If swallowed: Immediately call a doctor, a POISON CENTER. Do NOT induce vomiting.

If on skin: Immediately wash with soap and water for 15 minutes. Remove contaminated clothing and shoes immediately. Seek medical attention if irritation develops.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

If inhaled: Move to fresh air. If breathing is difficult, administer oxygen. If not breathing, administer artificial respiration. Seek immediate medical attention.

STORAGE:

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place.

DISPOSAL:

Dispose of contents and container in accordance with local, state, and national regulations.



FOUR WAY ACTION NC frees rusted and corroded screws, nuts, and bolts as well as aluminum and copper fittings. Use it to displace moisture on electronic and electrical equipment, protect metal, lubricate precision instruments and waterproof ignition systems and terminals.

DIRECTIONS:

SHAKE WELL BEFORE USING. Hold nozzle 6 to 8 inches from surface to be treated.

LOOSENS RUSTED NUTS & BOLTS:

Spray freely on to frozen nuts, bolts, parts and hinges and allow to penetrate up threads. Re-treat as necessary.

DISPLACES MOISTURE: Spray freely on electrical equipment. Let the product penetrate before attempting a re-start. Then, reapply for a protective lubricating coating.

INGREDIENTS/CAS#:

Mineral Oil (8042-47-5);
Carbon Dioxide (124-38-9);
Octamethylcyclotetrasiloxane
(556-67-2); Petroleum naphtha
(confidential).

NFPA® RATINGS:

Health: 1; Flammability: 1; Reactivity: 1

For industrial and commercial use only.

For additional information, see Safety Data Sheet.



WARNING: This product can expose you to chemicals including Cumene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.



Please Recycle.

8096.032025

Sold by:

Share Corp. • P.O. Box 245013 • Milwaukee, WI 53224 • (800) 776-7192 • www.sharecorp.com