

# Penetrating Oil Aerosol

## Penetrant & Rust Preventative

**Form:** Aerosol, Liquid  
**Color:** Colorless, Clear  
**Odor:** Solvent  
**pH:** N/A  
**Solubility (in water):** Negligible  
**Flash Point (ASTM D-7821):** N/A  
**Storage Stability (at 70°F):** 1 year

<u>This Product Contains:</u>	<u>CAS#</u>
Perchloroethylene	127-18-4
Kerosene	8008-20-6
Distillates (petroleum), Hydrotreated Light	64742-47-8
Naphtha	Proprietary

### Great For Use In...

- Battery Terminals
- Exhaust Systems
- Rusted Nuts/Bolts
- Brake Cables
- Pipe Fittings
- Speedometer
- Electrical Relays
- Parking Meters
- Locks
- Fuse Boxes
- Anywhere a multipurpose lubricant is needed

**Directions for Use:** Shake well before using. Hold nozzle 6 to 8 inches from corroded part. Saturate corroded area with PENETRATING OIL AEROSOL. Tap fitting lightly and allow several minutes to penetrate. Remove part. In some severe cases heating may be required.

### CONSULT PRODUCT LABEL FOR DETAILED DIRECTIONS

HMIS				NFPA	
		Severe	4	Extreme	
Health.....	3	Serious	3	High	Health.....
Flammability.....	2	Moderate	2	Moderate	Flammability.....
Reactivity.....	0	Slight	1	Slight	Reactivity.....
Personal Protection.....	C	Minimal	0	Insignificant	Special Precautions.....
					None