Metal parts won't corrode or lock when you coat them with **RYBS** from Share Corporation. This clinging lubricant contains moly, graphite and aluminum to prevent parts from seizing and galling when operating under intense heat and pressure. **RYBS** has been proven in temperatures ranging from -20°F to 2,000°F. When sprayed onto threaded components, **RYBS** provides a lubricating film between parts that prevents corrosion and seizing. It's an excellent general purpose lubricant for metal to metal contacts such as hinges and seals around boiler inspection ports. **RYBS** contains no chlorinated or fluorinated solvents.



DANGER:

Extremely Flammable Aerosol. Contains gas under pressure; May explode if heated. Causes skin and serious eye irritation. May cause respiatory irritation, drowsiness or dizziness. May be fatal if swallowed and enters airways.

PREVENTION:

Keep away from heat, sparks, open flames, and hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a wellventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection.

RESPONSE:

IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Avoid breathing fumes, mist, vapors, and spray. Use only outdoors or in a wellventilated area.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. IF SWALLOWED: Immediately call a poison center or doctor. Do NOT induce vomiting.

STORAGE: Store locked up.

DISPOSAL:

Dispose of contents and container in accordance with local, state, and national regulations.

INGREDIENTS/CAS#:

Heavy Naphthenic Petroleum Distillate (64742-52-5) Propane/n-Butane (68476-86-8) Heptane (142-82-5) Aluminum (7429-90-5)

NFPA[®] RATINGS:

Health: 1; Flammability: 3; Reactivity: 1

DIRECTIONS:

Surface must be free of dirt, grease and oil. Shake can for at least 30 seconds. In upright position, hold nozzle 8 to 10 inches from surface and apply by spraying **RYBS** in short bursts. Assemble and wipe off excess.

Sold by:

8229.021519

Share Corp. • P.O. Box 245013 • Milwaukee, WI 53224 • (800) 776-7192 • www.sharecorp.com

THICK CLINGING LUBRICANT PROTECTS AGAINST SEIZING • GALLING • CORROSION GALVANIC PITTING • RUST OF ALL THREADED PARTS

EXTREME TEMPERATURE

DANGER: EXTREMELY FLAMMABLE AEROSOL

Contains gas under pressure; May explode if heated.

Net Weight: 13 ounces (369 g)

See back panel for further cautions and first aid instructions.

KEEP OUT OF REACH OF CHILDREN